

RFCOMPONENTS.COM.AU



3.5 mm Attenuators

RFAB34-35-XX

DC - 34 GHz, 1 - 40 dB, 2 Watt 3.5 mm RF Attenuators

Rev

Impedance	50 ohm			
Frequency Range	DC-34 GHz			
VSWR	1.2 max			
Input Avg Power	2W@ 25°C ambient, derating linearly to 0.5W at 100°C			
Peak Power	200W (5 micro-sec pulse width, 1% duty cycle)			
Direction	Bidirectional, 3.5mm female to 3.5mm male (other configurations available)			
Attenuation(dB)	1-3	4-15	16-30	31-40
Accuracy(dB)	-0.4/+0.5	-0.5/+0.5	-0.5/+0.5	-0.6/+1.6


Mechanical

Connector Body	Passivated stainless steel
Heat Sink	N/A
Center Contact	1.27um Gold plated BeCu
Net Weight	About 3.5 g

Environmental

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 125°C
RoHS	Compliant
Temperature Coefficient	<0.0004 dB/dB/°C

Dimensions(mm)



RFAB34-35-2-XX-C

RFAB34-35-2-XX-B

RFAB34-35-2-XX-A

Notes

1. Customized dB values, outlines and optimal accuracy/VSWR available.

Model Description

RFAB34-35-2-XX-C

1. XX for dB value: 06=6dB, 30=30dB

2. Code for connector configuration:

A=female for two ends; B=male for two ends

C=female for one end and male for the other.